



Parts:

- | | | | |
|----|--------------------------------|----|---------------------------------|
| A) | High Profile Headrail — Steel | L) | Cord Tassels |
| B) | Pinion Rod (Tilt Rod) — Square | M) | Top Slat Clip |
| C) | Pinion Rod Cap | N) | Slats |
| D) | Tape Drum Support (Cradle) | O) | Bottomrail Plugs |
| E) | Tape Drum (Ladder Drum) | P) | Cord Grommets |
| F) | Cord Lock | Q) | 3 1/2" Royal Valance |
| G) | Cord Tilter | R) | Hold Down Brackets |
| H) | End Stiffener | S) | Hold Down Pins |
| I) | Cord Ladder | T) | Center Support Brackets |
| J) | Lift Cord 1.8mm | U) | Box Style Installation Brackets |
| K) | Bottomrail — Trapezoid | | |

System Features:

- Hidden 1-piece plastic valance clip

Blind (Material) Options:

- Fauxwood — Poly Vinyl Chloride (PVC) 2"
- 500 Hours UV Rated



Headrail:

- Polyester baked enamel — color coordinated
- Phosphate treated steel — 2" x 2" high
- Wall thickness — 0.018" (before paint)

Valance Options: (Color Coordinated)

- 3 1/4" Royal Valance for Fauxwood
- Inside Mount Optional Clip-On Returns — 1 1/4"
- Outside Mount Optional Clip-On Returns — 3 1/2"
- Hidden 1-part plastic valance clip

Bottomrail: (Color Coordinated)

- Trapezoid shape for tight slat closure

Tilt Controls:



Cord Tilt Option

- Acetal thermoplastic wheel to rotate smoothly and with minimal noise

Control Locations: (Restrictions may apply)

- Standard: Tilter — Left / Lift Cords — Right



Lift Control (Cord Lock):

- Snap-in design incorporates a stainless steel wear guard over which cords pass
- Incorporates "Crash Proof" safety feature that locks the blind automatically upon release of cords

Other Headrail Channel Hardware:

- Headrail components are made of low friction acetal thermoplastics
- Snap-in design of components allows for quick and easy repair if necessary



Cord Ladder: (Color Coordinated)

- Polyester braided cord ladders are designed to ensure proper control with adequate overlap of slats when in the closed position
- Options include:
 - Standard
 - Routless
 - Cloth Tape (Privacy Ladder)
 - Vinyl Tape (Privacy Ladder)

Cord Ladder Spacing:

- Maximum spacing between rout holes:
 - Fauxwood = 11"



Lift Cords: (Color Coordinated)

- 1.8mm Polyester braided cords designed for lifting and lowering the blind

Mounting Hardware:

- Universal box brackets (color coordinated)
- Center supports on blinds wider than 60"
- Extension brackets (when requested)
- Hold down brackets (when requested)



Size Recommendations:

- Minimum Width — 9"
- Minimum Drop — 9"
- Maximum Width — 96"
- Maximum Drop — 72"

The sizes listed above are merely recommendations. Blinds may be ordered larger if required. Optional 2 or 3 blinds on a single headrail are available as well.

Slats:

- Fauxwood
 - PVC Resin (base material), Methyltin Mercaptide (stabilizer), Calcium Carbonate (filler), Titanium Dioxide (UV inhibitor), Methyl Methacrylate (lubricant), Ethylenebis (lubricant), Octabenzene (UV inhibitor)
 - Lead Free
 - N.F.P.A. 701